



A compact valve box with 4 internal solenoid valves that connect to a 24Vac controller. Installation is uncomplicated and the eZyvalve®4 provides a trouble free way to distribute water to a micro irrigation system.

Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" BSP male threaded inlet and outlet connections.

Applications

Landscape, home gardens, greenhouses and nurseries. Above and below ground installation.



eZyvalve 4

| Performance | |
|----------------|-----------------|
| PRESSURE (kPa) | DISCHARGE (lpm) |
| 50 | 13 |
| 100 | 18 |
| 150 | 22 |
| 200 | 25 |
| 250 | 28 |
| 300 | 31 |
| 350 | 34 |

eZyvalve®4

| TYPE | ORDER CODE | PACK QUANTITY | PACKS PER CARTON | CARTON (kg) |
|--|------------|---------------|------------------|-------------|
| eZyvalve 4 - Valve Box 4 Solenoid Valves 3/4" BSPM 24Vac | 16605 | 1 | 10 | 10.1 |



Braided Hose

Accessories

| TYPE | ORDER CODE | PACK QUANTITY | PACKS PER CARTON | CARTON (kg) |
|----------------------------------|------------|---------------|------------------|-------------|
| BRAIDED HOSE 1000 mm x 3/4" BSPF | 90603 | 1 | 40 | 16.1 |
| TAP ADAPTOR 1" BSPF x 3/4" BSPM | 45825 | 25 | 30 | 12.0 |



eZyvalve 4 with Braided hose

Specifications

| DIMENSIONS PACKAGED | | CONNECTION TYPE | |
|---------------------|--------|-----------------|------------------------|
| LENGTH | 105 mm | Inlet: | 3/4" BSPM tapered |
| DEPTH | 182 mm | Outlet: | 3/4" BSPM parallel x 4 |
| WIDTH | 182 mm | | |
| WEIGHT (approx) | 1075 g | | |

| OPERATING SPECIFICATIONS | |
|--------------------------|---|
| FLOW | 1 L/min - 30 L/min |
| PRESSURE | 20 kPa - 1250 kPa |
| AMBIENT TEMPERATURE | 2°C - 60°C |
| ELECTRICAL | 24Vac, inrush current 320 mA, holding current 260 mA at 50 Hz |